

Ultra-Flo[®] MU08-8

Hollow Fibre Ultra-Filtration Membrane



System includes:

- U860 Ultra-Flo[®] membrane cartridge (8 cartridges)
- Feed and Backflush Pumps
- 2 control valves
- Feed, Air and Backflush Pressure Gauges
- Product Flow Meter
- Air-scouring blower
- Stainless Steel Frame
- PVC Piping, Hoses and Quick couplings
- Electrical Control Panel with PLC

Note: Ultra-Flo Pte Ltd reserves the right to make any changes to the information provided above without prior notice.

System & Operating Specifications:

Configuration	Hollow Fibre
Operation Process	Dead-end filtration (Out to In) Air scouring with backflush (In to Out)
Recovery	90 ~ 95 %*
Operating Temperature	< 50° C
Operating Pressure (TMP)	< 8 psi (Feed) <14 psi (Backflush)
Flow Rate (Per membrane)	
City Water	4.0 m ³ /h (56gfd)*
River/ Bore	2.5 m ³ /h (35gfd)*
Treated Wastewater	1.5 m ³ /h (21gfd)*
Product Turbidity	< 0.1 NTU *
Electrical Power	400V; 50Hz; 9A; Three Phase
Dimensions (Meter)	2.6 (L) x 1.2 (W) x 2.2 (H)
Weight	470 kg

* Subject to feed water condition



Ultra-Flo Pte Ltd
2 Tuas Avenue 10
Singapore 639126
Tel: +65 6457 7533
Fax: +65 6457 7517

